



ENDOT INDUSTRIES, INC.

PIPE AND TUBING • DUCT AND INNERDUCT

ENDOPOLY

200 PSI - PE 4710/PE 3408 WATER SERVICE TUBING (CTS) SPECIFICATION SHEET

CONFORMS TO THE FOLLOWING
APPLICABLE STANDARDS:

ASTM D3350	Cell Classification 445574C
ASTM D2737	Meets PE4710/PE3408 Requirements
NSF	Listed Under Standard 14 for Potable Water
AWWA C901-08	Conforms as 250 PSI & SODR 9 (CTS)
BOCA	Conforms as 200 PSI & SODR 9 (CTS)

WATER SERVICE TUBING (CTS) - ASTM D2737
STANDARD OUTSIDE DIAMETER RATIO (SODR) = 9

SIZE	NOMINAL O.D.	NOMINAL I.D.	MINIMUM WALL	WEIGHT PER 100 FT.	STANDARD COIL SIZE.
3/4	0.875	0.675	.097	10.0	500/100
1	1.125	0.865	.125	16.5	300/100
1-1/4	1.375	1.059	.153	24.8	300/100
1-1/2	1.625	1.253	.181	34.3	300/100
2	2.125	1.629	.236	59.2	200/100

WARRANTY

Limited Lifetime Warranty With 25 Year Cost of Replacement. See Warranty for Details

GUARANTEE

ENDOT pipe and tubing is guaranteed against rot, rust and electrolytic corrosion, and to be free from defects in material or workmanship. ENDOT's liability will be limited to the replacement of the pipe or tubing acknowledged to be defective.

ENDOT INDUSTRIES, INC.

www.endot.com - e-mail info@endot.com

CORPORATE HEADQUARTERS: 60 Green Pond Road, Rockaway, NJ 07866 – 800 443 6368 – FAX 973 625 4087

TENNESSEE OPERATIONS: 400 Bohannon Avenue, Greeneville, TN 37745 – 800 438 5851 – FAX 423 639 3722

OKLAHOMA OPERATIONS: Mid America Industrial Park, Pryor Creek, OK 74361 – 800 443 6368 – FAX 973 625 4087