



GENERAL NOTES:

1. FOR ADDITIONAL GENERAL NOTES, SEE DETAIL DU-01.
2. SEE "UNPAVED AREA TRENCH (UAT) (DU-02) DETAIL".

TRANSFORMER PAD NOTES:

1. TRANSFORMER PAD SET AT GRADE 1/4" PER FOOT ABOVE OR BELOW WATER METER SURFACE OR PLANS FOR RETAINING WALL SUBMITTED FOR REVIEW TO THE C.O.R.R..

STREET LIGHTING NOTES:

1. REFER TO SECTION 6 OF THE TRANSPORTATION CRITERIA MANUAL FOR DESIGN CRITERIA. GENERAL SPACING FOR STREET LIGHTING IN NEW DEVELOPMENTS IS AS FOLLOWS:
 - LOCAL ROADWAY (300-350 FOOT SPACING WITH 100 WATT LAMP)
 - COLLECTOR ROADWAY (250-300 FOOT SPACING WITH 100 WATT LAMP)
 - ARTERIAL ROADWAY (200-250 FOOT SPACING WITH 250 WATT LAMP)
2. IN ADDITION TO THE SPACING SHOWN ABOVE, STREET LIGHTS ARE ALSO PROVIDED AT OR NEAR INTERSECTIONS AND AT OR NEAR THE END OF CUL-DE-SACS.

RECORD SIGNED COPY
ON FILE

APPROVED

01-28-21
DATE

THE ARCHITECT/ENGINEER ASSUMES
RESPONSIBILITY FOR THE APPROPRIATE
USE OF THIS DETAIL.

CITY OF ROUND ROCK

STANDARD UTILITY ASSIGNMENTS
WITHIN RESIDENTIAL DEVELOPMENT
DETAIL

SCALE: NTS

DRAWING NO:
DU-06

SHEET 1 of 1